

Caltex® Protection for Construction Equipment



Hydraulic System

Rando® HDZ
Rando® HD
Torque Fluid 414 (CAT TO-4)
Delo® Silver 10W

Transmission

Delo® Synthetic Transmission Fluid 50 (Manual)
Delo® Trans Fluid ESI® (Manual)
Chevron Synthetic Automatic Transmission Fluid
Heavy Duty (Allison; TES-389)
Torque Fluid 454

Engine Crankcase

Delo® 400 LE 15W-40
Delo® 400 Multigrade 15W-40
Delo® XLE Multigrade 10W-40
Delo® Gold Ultra 15W-40

Coolant System

Delo® Extended Life Coolant
Caltex® Extended Life Coolant

Bearings and Grease Points

Delo® Grease EP 2
Ultra Duty Grease 2
Molytex® EP 2

Differential and Gear Drives

Delo® Synthetic Gear Lubricant 75W-90 (API GL-5/MT-1) and 80W-140
Delo® Gear Lubricant ESI® 80W-90 (API GL-5/MT-1) and 85W-140
Torque Fluid 454 (CAT TO-4)
Thuban® GL5 EP 80W-90 and 85W-140

A Chevron company product

The product recommendations provide general guidelines for use in construction. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. To contact your local Chevron Lubricant Distributor for confirmation of specific equipment OEM specifications, phone 0800 372 374.

© 2011 Chevron (New Zealand) Investment Co. Ltd. All rights reserved. All trademarks are the property of Chevron Intellectual Property LLC.

Delo®

DELO® DELIVERS CONFIDENCE™